



THE ZEBRA ET1 ENTERPRISE TABLET

IMPROVE SERVICE AND EFFICIENCY WITH THE ONLY TABLET THAT'S TRULY ENTERPRISE

Get the new class of tablet that is ready for business inside the four walls ' and out in the field. The ET1 stands out, with ingredients that make it truly ready for enterprise use. You get consumer-style sleek design and ease of use, with the enterprise durability required for all-day use inside and outside. And its enhanced Android operating system delivers enterprise-class security, flexibility and manageability over wireless LAN and wireless WAN networks.

Consumer styling with real business durability. On the outside, the ET1 is every bit as elegant as today's most popular tablets. Yet the ET1 is built for everyday use, able to handle drops, spills, chilly winter temperatures, extreme heat and more. And since the display is built with ultra-strong Gorilla® Glass, it is virtually impervious to damage, able to flex when dropped without shattering or scratching.

Use anywhere ' from retail to field sales and service with high-speed cellular/Wi-Fi wireless connections. Inside the four walls, support for 802.11a/b/g/n supports the fastest Wi-Fi networks for superior performance in your facility. And with a WWAN data-only modem, you get the flexibility to activate the ET1 on the high-speed 3G HSPA+ worldwide network for greater productivity out in the field.

Secure your data ' period. Whether your data resides on the internal drive or on removable media, it is encrypted, safe from hackers. So you can easily secure sensitive information, such as credit card data and patient information, to help comply with industry and government regulations.

Built for multiple users with feature-level control. With multi-user log-on, each worker is automatically granted access to their own personalized workspace ' the right applications and device features. And since managers know who is using the device at any time, task management is easier.

Add the features you need ' when you need them. With an expansion port and Bluetooth, you can add whatever peripherals you need, from scanners for easy inventory takes to magnetic stripe readers for payment processing.

Work uninterrupted ' power up and stay up. While most tablets in the industry only offer rechargeable batteries, the ET1 adds a removable battery that users can swap on the fly, preventing loss of data ' and productivity.

Easily build applications that run on the ET1 ' and your other Zebra mobile computers. The more operating systems you have, the more complex and expensive application development and maintenance can be. But with Zebra's RhoMobile Suite, you can easily create a single application that looks, feels and acts the same on Zebra mobile computers, regardless of whether it is built on the Android, Microsoft Windows Mobile or Windows CE operating system, reducing application development and support costs.

Protect your investment from the unexpected Service from the Start with Comprehensive Coverage provides true business-class support for your tablet. This all-inclusive optional service covers normal wear and tear, internal and external components damaged through accidental breakage for both device and select accessories and operating system issues ' keeping the ET1 up, running and in the hands of your users.

TURBOCHARGE YOUR WORKERS WITH A ZEBRA ET1 '

THE TABLET THAT'S TRULY ENTERPRISE.

For more information, please visit us on the web at www.zebra.com/et1 or access our global contact directory at www.zebra.com/contact

SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS		POWER	
Dimensions	5.14 in. H x 0.98 in. D x 8.82 in. W 130.5 mm H x 25.0 mm D x 224.0 mm W	Battery User Profile	Ample power for a full shift
Weight	WLAN: 1.4 lbs./ .63 kg; WWAN: 1.45 lbs./ .66 kg	Battery	WLAN: 4620 mAh rechargeable Smart Li-Ion; user replaceable; rapid resume
Display	7 in. capacitive; 1024 x 600; 350 NIT; Corning® Gorilla® Glass		WWAN: 5640 mAh rechargeable Smart Li-Ion; user replaceable; rapid resume
Touchpanel	Capacitive multi-touch		
Backlight	Ambient light sensor	DATA CAPTURE	
Keypad Options	Virtual; Bluetooth®	Rear Camera	Bar code scanning and image capture: 8MP autofocus camera with user controllable LED flash, illumination and aiming; captures 1D and 2D bar codes, photographs, video, signatures and documents
Expansion Capabilities	User accessible Micro SDHC card slot (up to 32GB); expansion module port	Front Camera	Optimized for video collaboration and low lighting conditions
Expansion Modules	Integrated expansion port for ' snap-in' peripherals for Zebra and third party peripherals	Video	720p video
Connectivity	Two USB interfaces: 1 USB 2.0 OTG connector (docking connector) and 1 USB 2.0 Host connector (expansion module port); HDMI out ; communication via cradle and expansion ports; USB 2.0 host via expansion module	Readability	9,000 ft. candles
Notification	LED flash; bar code decode	COMMUNICATIONS	
Audio	Stereo speakers and dual microphones (one front and one rear-facing)	WLAN	802.11a/b/g/n
PERFORMANCE CHARACTERISTICS		WWAN	WWAN data-only modem; works on 3G/HSPA+ carriers worldwide
		WPAN	Bluetooth 2.1 with EDR; integrated antenna
		GPS	WLAN: Autonomous GPS WWAN: Autonomous GPS with Assisted GPS (A-GPS)
		PERIPHERALS AND ACCESSORIES	
CPU	OMAP 4 Dual Core 1GHz x 2 + DSP		
Operating System	Android 2.3.4 enhanced with enterprise functionality; upgradeable to Android 4.x		

Memory	1GB RAM,4GB Flash plus 4GB microSD (total of 8GB flash memory); user accessible microSD card slot (supports up to 32GB)	Accessories include: scan/MSR module; scan module; protective rubber bezel; hip holster 1-slot docking USB charge cradle; 4-slot docking cradle charge only; 4-slot battery charger; power supply; USB/charge cable; 2-way DC cable; hand strap; headset; AC line cord; DC cable; battery; customizable bezel
---------------	---	---

USER ENVIRONMENT

Operating Temp.	32° F to 122° F/0° C to 50° C
Storage Temp.	-4° F to 158° F/-20° C to 70° C
Drop Specification	Multiple 4 ft./1.2 m drop per MIL STD 810G
Sealing	IP54
Vibration	4Gs peak, 5Hz to 2kHz, 1 hour duration per axis
Thermal Shock	-4° F to 158° F/-20° C to 70° C rapid transition
ESD	15kv Air, 8kv contact, 2kv charge body
Humidity	10% to 95% RH (non-condensing)
Development Tools	Zebra RhoElements for cross platform applications
Management Tools	Zebra Mobility Services Platform (MSP)

SENSORS

Gyroscope	Maintains orientation based on principles of conservation of angular momentum
Motion Sensor	3-axis accelerometer that enables motion-sensing applications for dynamic screen orientation and power management
Ambient Light Sensor	Automatically adjusts display brightness, keypad and display backlight
Electronic Compass	Independent ' does not depend on GPS

REGULATORY

For Regulatory information, please visit:
www.zebra.com/et1

RECOMMENDED SERVICES

Service from the Start with Comprehensive Coverage

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the ET1 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to:
www.zebra.com/warranty

REQUIREMENTS, NETWORKS, AND DATA PLANS ON



ZEBRA

Part number: SS-ET1-A4. Printed in USA 04/15. ©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES