



WT6400 Wearable Computer

Increase workflow efficiency and workforce productivity in demanding environments with the next generation in hands-free wearable computing

The WT6400 is the latest breakthrough in Zebra's wearable computer portfolio, packed with innovations that enable unmatched productivity increases in hands-free computing workflows. Next generation ergonomics bring a new level of comfort, flexibility and ease of use to workers picking orders, sorting goods and managing inventory in demanding environments, including the warehouse, distribution center and manufacturing plant. The touchscreen display area is twice the size of the WT6300¹, with only a minimal increase in device size. The powerful platform will support your business today and tomorrow, with a next generation Qualcomm processor, double the memory and support through Android™ 17. And data capture features include an integrated high-resolution 13 MP angled camera, support for Zebra Bluetooth® and corded scanners and a model with an innovative integrated keypad.



The next evolution in wearable ergonomics and comfort

More display real estate—yet compact and balanced

The WT6400 display has more than double the available area¹ than its predecessor, the WT6300—with minimal increases in overall device size and weight. The profile is nearly one third lower than the WT6300², substantially reducing bulkiness and making it easier to reach into tighter areas. And a lower center of gravity improves balance and substantially reduces arm fatigue.

Anywhere, anytime battery changes

The WT6400 battery is specially designed for easy changing on the fly. The angle of battery removal enables workers to remove and replace the battery with the most natural movement—no need to contort the hand or remove the WT6400 from the arm.

Effortlessly capture detailed photos

Taking a photo with the WT6400 is as easy as taking a photo on your cell phone. The high resolution 13 MP side camera is angled at 22°, keeping the display in the natural line of sight to ensure accurate aiming—no turning or twisting required, unlike other wearable computers. The result? Workers can capture proof of condition, proof of receipt and more in a split second.

Easy access to NFC

Other wearable computers embed the NFC radio in the battery, making it difficult for users to know where to tap. But NFC is integrated right into the WT6400 and clearly marked, so users can easily tap-to-pair a Bluetooth scanner or headset the first time—no guessing involved.

Choose the wearing style that suits your workers and your budget

Since the universal wrist mount supports all wrist straps, you can mix and match wrist straps to accommodate user preference and use case requirements. A single button releases the device from the wrist mount with snap-on and snap-off simplicity—so you can



The WT6400—the ideal wearable computer to take productivity and workflow efficiency to the next level in your operations.

For more information, please visit www.zebra.com/wt6400

give each worker their own wrist mount and wrist strap to prevent the spread of germs. Choose from cost-effective Velcro straps; a single dial strap that is micro-adjustable, allowing workers to simply turn the knob to find a perfect fit without pressure points; and a new dual dial strap that is ideal when using the keypad model, with two straps that provide a better grip on the arm and a more refined custom fit.

Flexible data entry options

Easy data entry with either hand—even with gloves

The WT6400 keypad model offers both a touch display and a physical keypad that is strategically placed below the display, where it is always in front of the user, equally accessible to right- and left-handed workers. Key size and spacing are optimized for any size fingers and heavy gloves. And placing the keypad under the display reduces the width of the device by nearly 20%³, creating a well-balanced, compact and comfortable footprint on any arm.

Add the wearable scanner of your choice

Choose the wearable scanner option that's right for your business and your workers—wireless Bluetooth or corded. There are three Bluetooth wearable scanner options. The 'open palm' RS2100 is the world's smallest enterprise wearable scanner. The flexible RS5100 offers five interchangeable wearing styles and two scan engine options. The RS6100 offers an extraordinary scanning range—from near contact to 40 ft./12.2 m—and can be used anywhere, including the freezer⁴. To connect a Zebra Bluetooth wearable scanner to the WT6400, just tap-to-pair on the NFC icon. And the rugged WT6400 side connectors are compatible with Zebra's high performance, rugged and freezer-ready⁴ corded RS5000 and RS4000 scanners.

Keep your workers connected and productive with all the right features

View all the information you need, at a glance

See more and scroll less with the large, bright 4.7 in. display that is easy to view in any lighting. Designed for use in just about any environment, the screen works when wet, with heavy gloves and in the freezer⁴.

Rugged and ready for your toughest environments

The WT6400 is ready for your most challenging environments—including the freezer⁴. It's drop-proof, tumble-proof, waterproof and dustproof, so you can use it just about anywhere. And since the display is one of the most vulnerable and crucial device features, it's protected with Corning® Gorilla® Glass Victus® 2—Corning's most scratch- and shatter-proof Gorilla Glass yet.

Wi-Fi™ you can count on

When it comes to Wi-Fi dependability, reliability and speed, the WT6400 stands out in its class. Ultra-fast Wi-Fi 6E provides more bandwidth, more capacity and the fastest available connections. And Zebra DNA Wireless Fusion provides advanced Wi-Fi radio hardware and software features that keep on-the-move workers connected and productive, every minute of the workday.

Power every minute of every shift

Both the standard and extended battery provide full shift battery power—and the extended freezer-rated⁴ battery is cold-chain ready. With hot-swap support, there's no need to power down for a battery change—and even if workers are mid-task, they won't lose data or their place in the workflow. And the blade connectors self-clean with every battery insertion or removal, improving reliability.

A faster, next generation platform

The next generation Qualcomm® processor and double the memory provide future proofing and the power to support the applications of today and tomorrow. With OS support through Android 17, you can count on access to the latest Android features for years to come. And with Zebra's LifeGuard™ for Android™ 5, you're always in charge of when and how to update. Allow device updates to happen automatically over the air for maximum security. Or, define which updates take place on which devices and when, allowing you to test applications to ensure compatibility—before you update.

Sustainability and extensibility

Good for the environment

From manufacturing to packaging, all the way to disposal, the WT6400 is designed for a sustainable life cycle. These devices are constructed with over 40% post-consumer recycled plastics—and without many major environmental toxins, such as Mercury and PFO/PFOAs. The Corning Gorilla Glass Victus 2 display is not only tough, but also sustainable, made from 22% recycled glass. Batteries are easily swappable and replaceable, while battery health insights allow you to replace your battery only when it is needed, reducing waste and unnecessary cost. In addition, the packaging is 90% biodegradable and uses recycled materials.

Simplify every stage of device lifecycle with Zebra DNA

This Zebra-only comprehensive collection of applications contains many ready-to-use tools at no cost that make the WT6400 easier to integrate, secure, deploy, manage and use. Make device management easier for IT personnel. Make Zebra devices even easier for workers to use with time-saving features that improve productivity and workflow efficiency. And easily deploy and manage all your Zebra DNA applications with Zebra DNA Cloud.

Specifications

| Physical Characteristics | |
|------------------------------|--|
| Dimensions | Touch Only: 5.22 in. L x 3.66 in. W x 0.55 in. D (132.5mm L x 93mm W x 13.97mm D) Touch + Keypad: 5.22 in. L x 4.21 in. W x 0.55 in. D (132.5mm L x 107mm W x 13.97mm D) |
| Weight | Without battery: Touch Only: 7.2 oz (205g) Touch + Keypad: 7.9 oz (223g) With standard battery: Touch Only: 9.8 oz (277g) Touch + Keypad: 10.4 oz (296g) With extended battery: Touch Only: 11.7 oz (331g) Touch + Keypad: 12.3 oz (350g) |
| Display | 4.7 in.; 720x1280; color display |
| Touch Panel | Capacitive touch panel; finger, gloved finger or conductive stylus support; Corning® Gorilla® Glass Victus® 2 |
| Power | Standard battery: typical capacity—3500mAh -4F to +122F (-20C to +50C) Extended battery (freezer rated*): typical capacity—5000mAh -22F to +122F (-30C to +50C) |
| Network Connections | WLAN (Wi-Fi); WPAN (Bluetooth); USB 2.0 (high-speed client and host) |
| Notifications | Audible tone; multi-color LED; haptic feedback |
| Keypad | 23 key alphanumeric/function (keypad model only) |
| Voice and Audio | Speaker; microphone; PTT voice |
| Buttons | Power button; touch-only model—three (3) programmable function buttons |
| Interface Ports | Two (2) rugged connectors (USB 2.0); two (2) charge pogo pads on each side |
| Performance Characteristics | |
| CPU | Qualcomm® QCS4490 octa-core; 2.4 GHz |
| Operating System | Android; for supported Android versions, visit: www.zebra.com/android-versions |
| Memory | 6 GB RAM; 64 GB Flash |
| Security | FIPS 140-3 ⁶ and FIPS 140-2 Validated; Common Criteria certified; Supports Secure Boot and Verified Boot |
| User Environment | |
| Operating Temperature | With standard battery: -4F to +122F (-20C to +50C) With extended battery (freezer-rated*): -22F to +122F (-30C to +50C) |
| Storage Temperature | -40F to +158F (-40C to +70C) |
| Drop Specification | Per MIL-STD 810H: 6 ft. (1.8m) to concrete at (+73F to +122F/+23C to +50C) 4 ft. (1.2m) to concrete across temperature (-22F to +122F/-30C to +50C) exceeding MIL-STD-810H |
| Tumble Specification | 1,000 Tumbles at 1.6 ft. (0.5m) at room temperature |
| Sealing | IP65; IP67 with battery per applicable IEC sealing specifications |
| Humidity | 5% to 95%, non-condensing |

| Vibration | 4g PK Sine (5Hz to 2kHz); 0.04g 2/Hz Random (20Hz to 2kHz); 60 minutes duration per axis, 3 axis |
|---|--|
| Electrostatic Discharge (ESD) | +/- 15kV air discharge; +/- 8kV direct/indirect discharge |
| Interactive Sensor Technology (IST) | |
| Light Sensor | Automatically adjusts display backlight brightness |
| Motion Sensor | 3-axis accelerometer with MEMS Gyro |
| Magnetometer | eCompass automatically detects direction and orientation |
| General Certifications | |
| Android Enterprise Recommended (AER) | Yes |
| Data Capture | |
| Scanning | Compatible with Zebra wearable Bluetooth scanners (RS2100, RS5100, RS6100) via NFC tap-to-pair and Zebra wearable corded scanners (RS4000, RS5000) via rugged side connectors. The RS5100 and RS6100 can be powered by the WT6400 using the corded adapter, with communication over Bluetooth. |
| Camera | 13 MP side camera |
| NFC | ISO 14443 Type A and B; FeliCa and ISO 15693 cards; NFC Forum cards 1 to 5 |
| Wireless LAN | |
| Radio | IEEE 802.11 a/b/g/n/ac/ax/d/h/i/r/k/v/w/mc; 2x2 MU-MIMO; Tri-band (2.4 GHz, 5 GHz, 6 GHz); Wi-Fi CERTIFIED 6™ (Wi-Fi 6E); Dual Band Simultaneous; IPv4, IPv6 |
| Data Rates | 2.4 GHz: 802.11b/g/n/ax—20 MHz—up to 286.8 Mbps; 5 GHz: 802.11a/n/ac/ax—20 MHz, 40 MHz, 80 MHz, 160 MHz—up to 2402 Mbps; 6 GHz: 802.11ax—20 MHz, 40 MHz, 80 MHz, 160 MHz—up to 2402 Mbps |
| Operating Channels | Channel 1-13 (2401-2483 MHz): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13; Channel 36-165 (5150-5850 MHz): 36, 40, 44, 48, 50, 52, 56, 60, 64, 100, 104, 108, 112, 114, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165; Channel 1-233 (5925-7125 MHz); Channel Bandwidth: 20, 40, 80, 160 MHz. Actual operating channels/frequencies and bandwidths depend on regulatory rules and certification agency. |

Markets and Applications

Warehousing

- Picking
- Sorting
- Receiving/put-away
- Replenishment
- Packing
- Reverse logistics (returns)

Manufacturing

- Inventory
- Put-away
- Line-side replenishment
- Work-in-Process (WIP) material Tracking and tracing
- Quality control
- Safety testing

| | |
|--------------------------------|--|
| Security and Encryption | WEP (40 or 104 bit); Enhanced Open (OWE); WPA/WPA2 Personal (TKIP and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES); EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP, EAP-PWD; WPA3 Enterprise 192-bit mode (GCMP256)-EAP-TLS |
| Certifications | Wi-Fi Alliance Certifications: Wi-Fi CERTIFIED; Wi-Fi CERTIFIED ac; Wi-Fi CERTIFIED 6 (Wi-Fi 6E); WPA2-Personal; WPA2-Enterprise; WPA3-Personal; WPA3-Enterprise (includes 192-bit mode); Protected Management Frames: Wi-Fi Enhanced Open; WMM (Wi-Fi Multimedia); WMM-Power Save; WMM-Admission Control; Voice-Enterprise: Wi-Fi Direct; Wi-Fi Agile Multiband; Wi-Fi QoS Management; Wi-Fi Optimized Connectivity; Passpoint |

Wireless PAN

| | |
|------------------|-------------------------|
| Bluetooth | Class 1; Bluetooth v5.3 |
|------------------|-------------------------|

Warranty

Subject to the terms of Zebra's hardware warranty statement, the WT6400 is warranted against defects in workmanship and materials for a period of one (1) year from the date of shipment. For complete warranty statement, please visit: www.zebra.com/warranty

Recommended Services

Zebra OneCare™ Essential and Select support services; Zebra Visibility Services—VisibilityIQ™ Foresight. For information on Zebra services, please visit www.zebra.com/services

Footnotes

1. Device display area is calculated by multiplying the length by the width of the display.
2. The WT6300 depth is .7 in. (17.78mm) and the WT6400 depth is .55 in. (13.97mm), making the WT6300 27.27 % deeper than the WT6400.
3. The WT6300 length is 6.25 in (158.7mm) vs. the WT6400 length of 5.22 in. (132.5mm), making the WT6400 19.5%+ less wide on the arm.
4. Freezer is defined as -30C (-22F) with WT6400 extended battery.
5. LifeGuard for Android is available with any Zebra OneCare support contract.
6. Applies to A14 release and subsequent OS release.

Specifications are subject to change without notice.

Zebra DNA

The Zebra DNA software suite makes your devices more powerful and easier to manage, with tools that ensure top performance, simple setup, and strong security. Zebra DNA for Mobile Computers is available on Android only. Features may vary by model and a Support Contract may be required. www.zebra.com/zebradna